



DGH1004XS



4CH H.265 NVR 1-HDD

○ SPECIFICATIONS*

Hardware	
IP Camera Input	4 Inputs
PoE	None
Video Output	1 VGA and 1 HDMI (up to 1080P) output
IP Camera Audio Input	4 Inputs
Two-way Audio Line-in	N/A
Audio Output	1 Output, RCA (2.0 Vp-p, 1kΩ)
Display & Decoding	
Video Format	H.265/H.264
Max. Input Bandwidth	40Mbps
Recording Resolution	5MP / 4MP / 3MP / 2MP (1080P) / 1.3MP (960P) / 1MP (720P)
Peak Decode Performance	2MP @80fps, VGA @120fps
Live / Playback performance	max 3ch 2592*1944@10fps max 4ch 2592*1520@10fps max 4ch 2048*1536@13fps max 4ch 1920*1080@20fps max 4ch 1280*720@30fps
SATA HDD Supported	1 HDD, up to 8TB
Network	
Network Interface	RJ-45 10/100Mbps self-adaptive Ethernet interfaces
Network Type	Static IP, DHCP, PPPoE
Supported Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Onvif Support	YES (Profile S, Profile G, Profile T)
Display Resolution	1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080
P2P Support	Yes, scan QR code to connect to NVR via mobile app
Cloud Storage Support	Yes, support to save pictures to Dropbox storage

Playback & Backup

Local Playback	Max. 4 Channels
Backup Method	USB, Network

Intelligent Features

IVA (Intelligent Video Analysis)	Perimeter Intrusion / Line Crossing / Stationary Objects / Pedestrian Detection / Face Detection / Cross Counting
AI Function	N/A

General

USB	USB 2.0 x2
e-SATA	N/A
RS-485 PTZ Control	N/A
Sensor & Alarm Port	N/A
Power Supply	DC 12V
Power Consumption (w/o HDD)	4W
Dimension (WxDxH)	300*209*47mm
Working Environment	-10°C~+55°C / 10%~90%RH

*The specifications are subject to change without notice.

REAR PANEL

