



DGM2216XS



1080P









Mobile H.265 Surveillance




2MP H.265 Eyeball IP Camera


O FEATURES

- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- ONVIF (OnviF) standard supported to simplify system integration
- DWDR to increase image recognizability in overexposure and dark areas
- Waterproof design on the Ethernet cable connector
- Remote Surveillance
 - Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system

O DIMENSIONS











O SPECIFICATIONS*

YES
10/100 Based-T Ethernet
TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
YES (Profile S, Profile G, Profile T)
(1) Multiple user access levels with password(2) IP address filtering(3) Digest authentication
Internet Explorer on Windows operating system
H.265 /H.264
Main-Stream: 1080P (1920x1080) Sub-Steam: VGA (640x480)
30fps
128Kbps ~ 4Mbps
Dual Stream (Main / Sub)
CBR / VBR
1/2.7" Progressive CMOS image sensor
Color 0.002Lux @(F1.2,AGC ON)
1/5 ~ 1/20000 sec
3.6 mm – F No. 2.2
Horizontal: 86°, Vertical: 47°, Diagonal: 105°
Micro SD slot, up to 256GB
Up to 30 meters
IR cut filter with auto switch
N/A
DWDR
YES
YES
YES
Auto
3D DNR
Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
Built-in microphone
NO
YES
YES (IEEE 802.3af)





12V / PoE ≤ 6W
≤ 6W
0.4
Ø100 x 90mm
iOS & Android mobile devices
YES
FTP / Email / SMS
YES
3 or higher, or equivalent AMD nics card, Direct Draw, 32MB RAM 10, Windows 8, Windows 7, Windows Vista & Windows XP, DirectX 9.0 or later

*The specifications are subject to change without notice.