



# DGM5156XS









Surveillance









## 5MP H.265 IR Fish Eye IP Camera

#### **O** FEATURES

- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- **ONVIF** (**OnviF**) standard supported to simplify system integration
- **DWDR** to increase image recognizability in overexposure and dark areas
- Waterproof design on the Ethernet cable connector
- **Remote Surveillance** 
  - -- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system

#### **O** DIMENSIONS





Dimensional tolerance: ± 5mm





### **O SPECIFICATIONS\***

| LAN Port  | YES  |
|---|--|
| LAN Speed   | 10/100 Based-T Ethernet  |
| Supported Protocols   | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP,                                 |
|   | SMTP, NTP, UPnP, SNMP, HTTPS, FTP  |
| ONVIF Compatible  | YES (Profile S, Profile G, Profile T)                                    |
| Security  | (1) Multiple user access levels with password                            |
|   | (2) IP address filtering   |
|   | (3) Digest authentication  |
| Remote Access   | Internet Explorer on Windows operating system                            |
| /ideo   |  |
| Network Compression   | H.265 /H.264   |
| Video Resolution  | Main-stream: (15fps) 5MP (2160×2160), 1520x1520, 1080x1080, 720x720      |
|   | Sub-stream: (15fps) 720x720, 480x480, 240x240                            |
| France Data   | Mobile-stream: (10fps) 480x480, 240x240                                  |
| Frame Rate  | 15fps  |
| Video bit rate  | 8Kbps ~ 8Mbps  |
| Multiple Video Streaming  | Triple Stream (Main / Sub / Mobile)                                      |
| General |  |
| mage Sensor   | 1/2.9" Progressive CMOS image sensor                                     |
| Min Illumination  | Color 0.1lux @ F1.2 (AGC ON); B/W 0 lux @ IR ON                          |
| Shutter Speed   | 1/5 ~ 1/20000 sec  |
| Lens  | 1.1 mm – F2.0  |
| Viewing Angle   | 360°   |
| SD storage  | YES  |
| R Effective Distance**  | Up to 5 meters   |
| R Shift   | IR cut filter with auto switch   |
| R LED   | 3pcs (SMD)   |
| Video Analytics   | NO   |
| WDR   | Digital WDR  |
| BLC   | YES  |
| ROI   | YES  |
| lmage Settings  | Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable |
| Audio   | Microphone, Speaker  |
| BNC Video Output  | YES  |
| Alarm Trigger   | YES  |
| Reset Button  | YES  |
| POE   | YES (IEEE 802.3af)   |
| Weather-proof   | IP66   |





| Operating Humidity                | 90 or less relative humidity   |
|-----------------------------------|--|
| Power Source (±10%)               | 12V / PoE  |
| Power Consumption (±10%)          | ≤ 5W   |
| Net Weight (kg)                   | 0.4  |
| Dimension                         | Ø120*55mm  |
| Others                            |  |
| Mobile Surveillance               | iOS & Android mobile devices   |
| Motion Detection                  | YES  |
| Event Notification                | FTP / Email / SMS  |
| RTC (real-time clock)             | YES  |
|                                   | ·Intel core i3 or higher, or equivalent AMD ·2GB RAM   |
| Minimum Web Browsing Requirements | AGP graphics card, Direct Draw, 32MB RAM   |
|                                   | ·Windows 10, Windows 8, Windows 7, Windows Vista & Windows XP, DirectX 9.0 or later ·Internet Explorer 7.x or later (Windows Edge not supported) |

 ${}^{\star}\mathsf{The}$  specifications are subject to change without notice.